



HITEC-LM-060-Ka

6 meter limited-motion Ka-band
Satellite Ground Antenna System

KEY FEATURES

High accuracy under adverse environmental conditions for high performance operation in Ka-band frequencies

Large working platform and stairs combined with supersized center-hub for housing RF equipment and improved accessibility

Standalone system with all antenna components (e.g. power electronics) integrated in its structure

Equipped with an Antenna Front Panel, which allows global health and status monitoring, as well as commanding of the auxiliary functions (e.g. HVAC, de-icing) through a single interface

Multiple options:

- HVAC
- De-icing system
- Hand-cranking
- Logging system
- 19" racks
- HPA supports etc.

The LM-060-Ka is a low maintenance and future proof antenna system designed for robust, reliable and high performance operation for geostationary Ka-band applications. The LM-060-Ka can accommodate different feed systems and can operate at different frequencies, depending on the application.

The reflector, 6.8 m in diameter in a dual shaped Cassegrain configuration for high efficiency, is constructed of precision bonded aluminum panels and can be adapted to diameters from 6.0 to 7.5 m. The backup structure consists of aluminum framework trusses, reinforced by a structural plenum. This configuration ensures optimum rigidity and surface accuracy under self-weight and environmental effects and can accommodate the optional de-icing system.

The antenna hub has generous interior dimensions (W x H x D: 1745 mm x 1545 mm x 975 mm) and allows placing up to 29 units of 19" racks (600 mm depth) and installing all converters and high-power amplifiers right next to the feed. Easy access to the equipment is ensured by a large opening covered by roller shutters.

The LM-060-Ka is equipped with the HITEC Luxembourg Antenna Control Unit HACU-1000, providing program track functionality as a baseline. Depending on customer requirements and the installed RF equipment, a step-track or monopulse capable version of the HITEC Luxembourg ACU can be installed.



Copyright © 2013 HITEC Luxembourg S.A. All rights reserved.
HITEC Luxembourg and the HITEC Luxembourg logo are registered trademarks of HITEC Luxembourg. Specifications and fact sheets are subject to change without notification.

Version 09/2013

ANTENNA SYSTEM CHARACTERISTICS: HITEC-LM-060-Kc

SYSTEM PERFORMANCE

Tracking:	Program Track Step Track (*) Monopulse (autotrack) (*)
Frequency bands:	Designed for Ka-band (18.8 - 31.0 GHz) Adaptable to Ku-band (10.7 - 18.4 GHz)
Antenna gain (ref. feed horn):	> 64.1 dBi @ 27 GHz approx. $20 \cdot \log_{10}(f[\text{GHz}]) + 35.5$
Antenna noise temperature (ref. feed horn):	148.0 K @ 5° Elevation 93.0 K @ 10° Elevation 44.0 K @ 30° Elevation
Radiation pattern:	Complies with ITU-R S.456, S.580, S.732
Accuracy:	Tracking, no wind: (*) Pointing, no wind: 0.012° Tracking, op. limit: (*) Pointing, op. limit: 0.022°

ANTENNA OPTICS

Configuration:	Cassegrain optics
Reflector diameter:	Designed for 6.8 m Adaptable to other diameters from 6.0 m to 7.5 m
Reflector surface accuracy:	< 0.3 mm RMS
3dB Beamwidth:	0.104° @ 27 GHz

FEED SYSTEM

Various feed systems can be installed following detailed customer specifications.

HUB CHARACTERISTICS

Available space for housing RF equip- ment	~ 1.7 m x 1.5 m x 0.95 m
Environment	Closed sealed space Temperature controlled (*)

AXIS DESIGN

Limited motion elevation over azimuth mount
Dual backlash compensated drives on azimuth
High precision roller screw on elevation
Controlled polarization axis (*)

ELEVATION

Operational travel range:	-1 to 91 deg
Maximum rate:	0.25 deg/sec High-speed option: 0.5 deg/sec

AZIMUTH

Operational travel range:	180 deg
Maximum rate:	0.5 deg/sec High-speed option: 1 deg/sec

ENVIRONMENTAL CONDITIONS

Drive limit:	130 km/h
Wind operational limit:	Mean 90 km/h Peak 110 km/h
Survival wind:	200 km/h
Temperature:	Operational -20°C to +40°C optionally -30°C to +50°C Survival -35°C to +60°C
Rain:	Max. 100 mm/h
Power supply:	3 x 400 V short-break (**) 3 x 400 V no-break (**)
Snow (build up):	1000 kg
Corrosion:	Region: Coastal and polar

OPTIONS

HVAC
De-icing system
Feed blower
Hand-cranking
Logging system
19" racks
HPA supports
Motion warnings
Aircraft warning lights
Dehydrator

(*) Optional, depending on customer selected configuration

(**) Consumption depending on customer selected configuration

CONTACT

HITEC Luxembourg S.A.
5, rue de l'Eglise
L-1458 Luxembourg
www.hitec.lu

Tel: +352 498478-1
Fax: +352 401303
info@hitec.lu
www.hitec-luxembourg.com

